

ZERO STAT-DiamondSeal  
Material Safety Data Sheet

SECTION I - IDENTITY

ZERO STAT-DiamondSeal	
	Hazardous - NO
Ground Zero	
4916 26th Street West	Health   1
Suite 100	Flammability   0
Bradenton, FL 34207	Reactivity   0
	Personal Protection   B
Telephone Number for Information	
941-751-7581	4 = Most Hazardous
Date Prepared	Emergency Phone Number
02/10/00	Poison Center
Prepared By T. Pitrolffy	

SECTION II - HAZARDOUS INGREDIENTS

Hazardous Components CAS Reg#	PEL	TWA	STEL	Other Limits	%
Not a hazardous mixture, as defined in 29 CFR 1910,1200 and M.G.L. c. 111F	--	--	--	--	(opt)
CONTAINS: GLYCOL ETHERS*					<6
*CHEMICAL CATEGORY SUBJECT TO REPORTING REQUIREMENTS OF SEC.313, TITLE III.					

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling point	- 218F	Specific Gravity (Water=1)	- 1.05
Vapor Pressure (mm Hg)	- 18	Melting Point	- NA.
Vapor Density (air=1)	- 1.1	Evaporation Rate (Butyl Acetate=1)	- .36
Viscosity (CPS)	- 15	Decomposition Temperature	-NA.
Auto Ignition Temp.	- NA.	Solubility in Water	-Complete
pH	- 8.7 +/- .5		
Appearance and Odor	-Light blue milky liquid		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point	- None	Flammable Limits	
		LEL	UEL
		- NA	- NA
Extinguishing media	- NA		
Fire Fighting Procedure	- NA		
Fire and Explosion Hazards	- NA		

SECTION V - REACTIVITY DATA

Stability - Stable  
Conditions to Avoid - Freezing, extreme heat

Incompatibility - Acids, oxidizers  
Hazardous Decomposition or Byproduct - Thermal decomposition may yield carbon monoxide  
Hazardous Polymerization - Will not occur  
Conditions to Avoid - NA

The information herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or results to be obtained from use thereof.  
Essentially similar to OSHA form # 174

---

SECTION VI - HEALTH HAZARD DATA

---

Routes of entry:

Inhalation - NO                      Skin - NO                      Ingestion - NO

Health Hazards-Acute: Causes eye and skin irritation

CHRONIC:Redness of skin

Carcinogenicity: NO

NTP - NA                      IARC Monographs - NA                      OSHA Regulated - NO

Signs and Symptoms of Exposure - Itching irritating sensation

Medical Conditions Aggravated - NA

Emergency and First Aid Procedures - Wash contact areas with soap and water

INGESTION:Drink milk, water, fruit juice, induce vomiting with oil of  
ipecac, get medical attention.

---

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

---

Steps to be Taken in Case Material is Released or Spilled - Dike, collect  
material into watertight container, rinse surface with clean water.

Waste Disposal Method - Use sanitary landfill disposal, (not a hazardous  
waste) according to federal, state and local regulations. (RCRA, Subtitle  
D.)

Precautions to be Taken in Handling and Storage - Do not mix with other  
chemical, store away from heat. KEEP FROM FREEZING.

Other Precautions - KEEP AWAY FROM CHILDREN

---

SECTION VIII - CONTROL MEASURES

---

Respiratory Protection - Not required with normal use.

Ventilation            Local Exhaust - NA  
                          Mechanical        - NA  
                          Special            - NA  
                          Other              - Assure fresh air circulation

Protective Gloves - RECOMMENDED: Rubber, Plastic

Eye Protection        - RECOMMENDED: Safety glasses

Other Protection     - NA

Work/Hygienic Practices - Do not eat or drink next to material, wash hands  
after work.

---

SECTION IX - TRANSPORTATION

49 CFR

---

Unit Cont. - 55,30,5,1 GAL. PLASTIC CONT                      Report Qty. (Lbs) - NA.

OSHA - NOT REGULATED.    Labels - NO.

DOT - NOT REGULATED.

UN - NOT REGULATED.

---

Vendor assumes no responsibility for injury to vendee or third person proxim-  
ately caused if reasonable safety procedures are not adhered to as stipulated  
in the data sheet. Additionally, vendor assumes no responsibility for injury  
to vendee or third persons proximately caused by abnormal use of the material  
even if reasonable safety procedures are followed. Further more, vendee  
assumes the risk in use of the material.