



STOPESD affordable ESD solutions **ION – 160 SELF BALANCING IONIZER**

SELF BALANCING IONIZER – S-ION – 160



The S-ION-160 is a highly reliable blower for static elimination featuring a variable speed fan, an integral air flow diffuser, as well as a separately controlled heater for operator comfort, when required. The unit provides a powerful airflow with a very low noise level. Its support stand makes it mountable on walls, pedestals, or overhead.

SPECIFICATIONS

Ion Balance	Self balancing unit. Maintains 0 volts \pm 5 volts balance at all normal operating conditions.
Air Volume	Variable 38 to 76 liters/second (80 to 160 cubic feet/min).
Air Velocity	2.8 m/sec at 0.6 meters (550 ft./min at 2 ft.) at maximum fan speed.
Ionized Air Coverage Angle	60 Degrees
Heated Air	
@ Minimum Airflow	8.8°C (16°F) rise above ambient.
@ Maximum Airflow	4.4°C (8°F) rise above ambient.
Noise Level	63 d.b.a. max at 0.6 meters (2 feet) @ max. air speed.
Ozone	Per UL 867 requirements.
EMI/RFI	Complies with FCC part requirements for class-A equipment.
Dimensions	254 X 305 X 159 mm. (L X W X H) 10 X 12 X 6.25 in.
Footprint of Stand	324 X 140 mm. (12.75 X 5.5 in.)
Weight	3.6 kg. (8 lbs.)
Line Voltage	115 VAC or 230 VAC, 50/60 Hz.
Power	35 Watts with heater off, 435 with heater on.
Fuse.	115 VAC unit supplied with 2.5 amp fuse 230 VAC unit supplied with 2.5 amp fuse.
CE Compliant	Yes, order S-ION-160-CE.



P.O. Box 19338, Rye, CO 81019
Direct: 719-676-2544 **Fax:** 719-676-2549
Email: sales@stopesd.com
www.stopesd.com