

Material Safety Data Sheet

SECTION I - IDENTITY

	#22 SEAL II	Hazardous - NO
Ground Zero	-----	
4916 26th Street West	Health	1
Suite 100	Flammability	1
Bradenton, FL 34207	Reactivity	0
	Personal Protection	B
	-----	
Telephone Number for Information	4 = Most Hazardous	
941-751-7581	Emergency Phone Number	
Date Prepared	Poison Center	
11/14/02		
Prepared By T. Pitrolffy		

SECTION II - HAZARDOUS INGREDIENTS

Hazardous Components CAS Reg#	PEL	TWA	STEL	Other Limits IDLH	% (opt)
2-BUTOXYETHANOL #111-76-2*	50	25	N.A.	700ppm	<10
DIETH. GLYCOL METH. ETHER* # 111-77-3	N.A.	N.A.	N.A.		< 7
ISOPROPANOL # 67-63-0	400	400	500	12000ppm	< 6

\*LISTED CHEMICAL SUBJECT TO REPORTING REQUIREMENT OF SCT.313 OF TITLE III.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling point	- 210	Specific Gravity (Water=1)	- 1.01
Vapor Pressure (mm Hg)	- 0.6	Melting Point	- N.A.
Vapor Density (air=1)	- 2.1	Evaporation Rate (Butyl Acetate=1)	-0.3
Viscosity (CPS)	- 375	Decomposition Temperature	-NA.
Auto Ignition Temp.	- NA.	Solubility in Water	-COMPLETE
pH	- 6.5 +/- .5		
Appearance and Odor	-LIGHT COLORED MILKY LIQUID, GLYCOL ODOR		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point	- TCC 142 F.	Flammable Limits	
		LEL	- N.A.
		UEL	- N.A.
Extinguishing media	- WATER SPRAY		
Fire Fighting Procedure	- COOL CONTAINERS WITH WATER		
Fire and Explosion Hazards	- SLIGHT		

SECTION V - REACTIVITY DATA

Stability - STABLE  
 Conditions to Avoid - N.A.

Incompatibility - ACIDS, BASES, STRONG OXIDIZERS  
 Hazardous Decomposition or Byproduct - THERMAL DECOMPOSITION MAY YIELD  
 CARBON MONOXYDE

Hazardous Polymerization - WILL NOT OCCUR  
 Conditions to Avoid - N.A.



---

Vendor assumes no responsibility for injury to vendee or third person proximately caused if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Further more, vendee assumes the risk in use of the material.